

FOC-SS

Fiber Optic Cleaver



- Designed for fiber cleaving applications that include field termination of fiber connectors and mechanical splices as well as laboratory applications
- Small, lightweight and easy to use
- Features a graduated leaf spring scale, which allows cleave lengths of 2.0 mm to 20.0 mm
- The "Score and Snap" leaf spring function is easy, fast and is the preferred method by many fiber installers
- Produces a precise cleave endface angle of less than 2 degrees
- Supplied with a standard carbide cleaving blade capable of over 6,000 consistent cleaves
- Cleaving tool is designed for single mode and multimode fiber with cladding O.D. diameter of 125 micron with no operator tool adjustments
- Cleaver and instructions come in a 2.12 oz (60g) hard plastic case that measures 5.38 x 3.38 x 1.13 in. (137 x 86 x 29 mm)
- Cleaver Dimension: 4.88 x 0.79 x 1.57 in. (124 x 20 x 40 mm)
- Weight: 2.12 oz (60g)
- **Fiber Optic Cleaver: FOC-SS**
Part No.: 46490
- **Leaf Spring Replacement: FOC-LS**
Part No.: 46492
- **Carbide Blade Replacement: FOC-CBL,**
Bladelife scores – 6,000*
Part No.: 46491
- **Diamond Blade Replacement: FOC-DBL,**
Bladelife scores – 10,000*
Part No.: 46493
- Made in the U.S.A.
- * Based on no damage or chipping to blade

RMC-6

Ruler

- Precision quality stainless steel 6 in. (150 mm) ruler
- Sliding clip for pocket attachment and depth gauge use
- One ruler side indicates inches and mm and one side indicates 64th and mm conversions
- Ideal addition for fiber kits as well as other specialty tool kits
- Made in the U.S.A.
- Weight: 1.0 oz (28 g)
- Length: 6.4 in. (163 mm)
- Part No.: 80683

