



OH 50 A



Gallery



Packaging data

Sales unit	1 pcs.
Packaging volume shipping package	31.5 dm ³
Gross Weight shipping unit	7.64 kg
EAN	4010056730116
Article number	73011
Customs tariff number	85437090

Technical data

Frequency range TV	47...862 MHz (output combiner/amplifier)
Frequency range FM	87.5...108 MHz (FM-amplifier)
Input level FM	70...100 dB μ V
Gain FM	25 dB
Attenuator FM	30 dB (1 dB-steps)
Output level	110 dB μ V
Output attenuator	0...15 dB
Output test jack	-20 dB

Connectors

Module slots	14 pcs. (OH-module)
F-socket	3 pcs. (FM-input, output, output measurement socket)
USB	1 pcs. (Software-Update, Konfiguration)
RJ11	1 pcs. (OH 41)
RJ45	1 pcs. (remote monitoring and programming)

General data

Operating voltage AC	180...265 V (47...63 Hz)
Power consumption	<185 W
LNB supply voltage	12.5 V
LNB electrical power supply	1.2 A
Dimensions (width x height x depth)	443x132x351 mm (3 HE)
Operating temperature range	-20...+50 °C

Title

OH 50 A

Short description

Compact Headend basic unit, 230 V AC, 19", 3 HE, for 14 modules

Description

Compact Headend basic unit, 230 V AC, 19", 3 HE, for 14 modules

Base unit OH 50 for analog und digital channel processing headends

Slots for up to 14 modules (14 analog or 28 digital channels)

19"- rack-mounting or wall mounting

Integrated FM amplifier

Simple programming with handset OH 41 (OK 41 A)

Preprogramming via USB-connection (USB-Stick)

Integrated remote supervision moduel OH 51 A (license optional)

High output power



OH 50 A

