



VX 67 B



Packaging data

| | |
|-----------------------------------|---------------------|
| Sales unit | 1 pcs. |
| Packaging volume shipping package | 1.2 dm ³ |
| Gross Weight shipping unit | 0.87 kg |
| EAN | 4010056715960 |
| Article number | 71596 |
| Customs tariff number | 85437030 |

Technical data

| | |
|-------------------------------------|---|
| Downstream | |
| Inputs | 1 pcs. |
| Frequency range DS | 85...1006 MHz |
| Gain DS | 6 dB |
| Output level 1 | ≥87 dBμV (CENELEC 42 channels, flat, at CSO/CTB >60 dB) |
| Return path | |
| Frequency range US | 5...65 MHz |
| Amplifying US | 1 dB |
| Noise figure US | ≤18 dB |
| Output level 4 | 116 dBμV (DIN. IMA2/3 >50 dB) |
| Connectors | |
| F-socket | 5 pcs. |
| General data | |
| Operating voltage AC | 230 V (±10 %) |
| Power consumption | 3 W |
| Screening factor | dB Class A, EN 50083-2 |
| Dimensions (width x height x depth) | 165x105x45 mm |
| Operating temperature range | -25...+75 °C |
| Protection class | IP20 |

Title

VX 67 B

Short description

In-house amplifier

Description

In-house amplifier

Long text

Adjustable level and equalizer

F-connectors

Wall mounting

Metal housing