

## Čtyřnásobné odbočovače



Frekvence MHz	TP124- 8T	TP124- 11	TP124- 14	TP124- 17	TP124- 20	TP124- 23	TP124- 26	TP124- 29
<b>Průchozí útlum dB maximum</b>								
5-47	T	3,4	2,4	1,6	1,4	1,0	0,9	0,9
47-470	T	3,5	2,3	2,0	1,6	1,3	1,2	1,3
470-862	T	4,6	3,1	2,1	2,0	1,5	1,4	1,4
862-1000	T	5,5	4,1	3,1	2,5	2,1	1,9	1,9
<b>Odbočovací útlum dB (+/- 1.5 dB)</b>								
5-862	8	12	14	17	20	23	26	29
862-1000	8	12	14	17	20	23	26	29
<b>Izolace výstup - odbočení dB minimum</b>								
5-47	T	19	20	20	22	30	32	34
47-470	T	22	26	26	31	33	36	34
470-862	T	24	29	27	29	29	32	32
862-1000	T	19	25	22	24	26	29	29
<b>Izolace odbočení - odbočení dB minimum</b>								
5-47	19	16	17	20	19	21	21	21
47-470	25	20	19	22	22	22	24	22
470-862	22	20	21	21	21	21	21	21
862-1000	19	19	19	19	19	19	19	19
<b>Útlum odrazu vstup - výstup dB minimum</b>								
5-47	19	16	17	17	17	19	19	19
47-470	19	18	17	18	19	19	19	19
470-862	17	17	16	17	16	16	17	17
862-1000	17	14	15	15	15	15	15	15
<b>Útlum odrazu odbočení dB minimum</b>								
5-47	17	16	17	17	17	17	17	17
47-470	19	18	18	18	19	19	18	18
470-862	17	17	17	17	17	17	17	17
862-1000	15	15	15	15	15	15	15	15

<b>Frekvenční rozsah</b>	do 1 GHz
<b>Konektory</b>	5/8
<b>Impedance</b>	75 Ω
<b>Pouzdro</b>	IP 67
<b>Provozní teplota</b>	-10 ... +55 °C
<b>Skladovací teplota</b>	-30 ... +70 °C
<b>ECM</b>	EN 50083-2, Třída A
<b>Nízkofrekvenční rušení</b>	-60 dB @ 10A 60VAC
<b>Maximální proud</b>	12A @ 90 VAC



Vyžlovská 3111 / 16, 100 00 Praha 10  
 tel.: 274 773 917, fax: 274 816 437  
 E-mail: [inkat@inkat.cz](mailto:inkat@inkat.cz)