

Multiodbočovače



Multiodbočovače DMV

Typ	DMV5T	DMV4
Frekvence (MHz)		
Průchozí útlum (dB max.)		
5-65	-	$3,8 \pm 0,8$
65-470	-	$3,9 \pm 0,8$
470-1000	-	$3,9 \pm 0,8$
Odbočovací útlum (dB)		
5-1000	12,5 / 12,5 / 12,5 / 12,0 / 12,0 $\pm 1,0$	12,5 / 13,5 / 14,5 / 15,5 $\pm 1,0$
Izolace odbočení-výstup (dB min.)		
5-65	-	26
65-470	-	30
470-1000	-	26
Izolace odbočení-odbočení (db min.)		
5-65	40	40
65-470	40	40
470-1000	36	36

Typ	DMV8	DMV6
Frekvence (MHz)		
Průchozí útlum (dB max.)		
5-65	9,0 ± 1,0	6,8 ± 1,0
65-470	9,0 ± 1,5	6,9 ± 1,0
470-1000	9,0 ± 1,5	6,9 ± 1,5
Odbočovací útlum (dB)		
5-1000	12,5 / 13,5 / 14,5 / 15,0 / 16,0 / 17,0 / 18,0 / 19,0 ± 1,0	12,5 / 13,5 / 14,5 / 15,5 / 16,5 / 17,5 ± 1,0
Izolace odbočení-výstup (dB min.)		
5-65	26	26
65-470	30	30
470-1000	26	26
Izolace odbočení-odbočení (db min.)		
5-65	40	40
65-470	40	40
470-1000	36	36
Konektory	F	
Impedance	75 Ω	
Pouzdro	IP 64	
Rozsah provozních teplot	-10 ... +55 °C	
Skladovací teplota	-30 ... +70 °C	
ECM	EN 50083-2	



Vyžlovská 3111 / 16, 100 00 Praha 10
tel.: 274 773 917, fax: 274 816 437
E-mail: inkat@inkat.cz